



MARINE



✓ EFFICIENT

✓ LIGHT

✓ POWERFUL

THE NEXT BEST THING TO SAILING

LIGHT WEIGHT

28kg-33kg

EFFICIENT

Up to 93% efficiency

RELIABLE

Limited moving parts

ECO FRIENDLY

No emissions
No fuel

POWERFUL

Available in 28v and 48v

LOW COST

Save on fuel bills

SAILFISH SONIC ELECTRIC DRIVE SYSTEM

Overview

The Sailfish comes in two different models with a 24V and 48V system built in to suit a range of vessels ranging from pleasure craft to catamarans.

Key Features

- 2 models available (Direct Drive 1:1 and Reduction Drive 2:1)
- Simple to install
- Quiet to run
- No diesel smell
- Cheaper to fit
- No wet exhaust
- Power: 5-35HP

Sailfish Sonic Electric Drive Systems



? Our Models

Direct Drive

- ✓ Power: 5-10HP
- ✓ 24v Input
- ✓ 2.5Kw Output
- ✓ Approx weight 28kg

Reduction Drive 2:1

- ✓ Power: 10-35HP
- ✓ 48v Input
- ✓ 8Kw Output
- ✓ Approx weight 33kg

Applications



Pleasure craft



Sailing boats



Lynch Motor Company Ltd.
Unit 4 Flightway Dunkeswell, Honiton, Devon, EX14 4RD
Tel: +0044 (0)1404 892940
Fax: +0044 (0)1404 891990
info@lynchmotors.co.uk



SAILFISH

SONIC ELECTRIC SAILDRIVE

? Whats included?

Motor complete with controller and operating lever, shunt box, wire and connectors.

✓ EFFICIENT ✓ LIGHT ✓ POWERFUL

THE NEXT BEST THING TO SAILING

Direct Drive Model (Yellowtail Control System 5-10HP)

For use with Lynch Yellowtail 2.5 Direct Marine Drive System (24V - 2.8kw.)

Propeller max. diameter

- ✓ 2 blade fixed : 15"/381mm
- ✓ 3 blade fixed : 14"/356mm
- ✓ 2 blade folding : 15"/381mm

Propeller shaft options

- ✓ Ø 28mm - 17 spline
- ✓ Ø 25mm - 1 in 10 taper

LM6 Aluminium or Gunmetal
Bronze lower unit

Approx weight with motor

- ✓ Aluminium 28kg / Bronze 35kg

Reduction Drive Model 2:1 (Marlin Control System 10-35HP)

For use with Lynch Marlin Single Drive System (48V-8kw to special order.)

Propeller max. diameter

- ✓ 2 blade fixed : 17"/432mm
- ✓ 3 blade fixed : 16"/406mm
- ✓ 2 blade folding : 16½"/419mm

Propeller shaft options

- ✓ Ø 28mm - 17 spline
- ✓ Ø 25mm - 1 in 10 taper

LM6 Aluminium or Gunmetal
Bronze lower unit

Approx weight with motor

- ✓ Aluminium 33kg / Bronze 40kg

BMV 700 INTELLIGENT DISPLAY

Key ignition with voltage, battery capacity and available range.



BMV 712

Monitors battery condition remotely through the app.

STANDARD THROTTLE

One direction setting or neutral position with forward and reverse. Can be top or side mounted.



SIGMA DISPLAY

Key ignition with battery capacity levels, throttle settings and programme codes for the controller.



LYNCH DUAL THROTTLE

To use with Catamarans and Twin Prop applications.



THRUST BEARING



DC TO DC CONVERTOR

